












CODIGO PK	PKSS6060BC3
-----------	-------------

DATA SHEET/ FICHA TECNICA

NAME OF SERIES OR ITEM NUMBER	
MATERIAL (CERAMIC, PORCELAIN, DOUBLE LOADING, SOLUBLE SALT, SALT&PEPER, OTHER)	SOLUBLE SALT/ SAL SOLUBLE
SUPERFICIE (ROUGH OR POLISH)	POLISH/ PULIDO
TECNIC (ROTO COLOR, INJECT, OTHER)	IVORY
LAST UPDATE	13 jun 2019

TECHNICAL CHARACTERISTICS CARACTERISTICAS TECNICAS		PORCELAMIK VALUES / VALORES	NORMA ISO 13006 /EN 176 GROUP Bla REQUISITOS / REQUIREMENTS	TEST METHOD AS PER IOS NORM TEST DE ACUERDO A
	LENGTH AND WIDTH DIMENSIONES (MM)	±0.1%	±0.5%	UNI EN ISO 10545-2
	STRAIGHTNESS OF SIDE RECTITUD LATERAL (MM)	±0.1%	±0.5%	UNI EN ISO 10545-2
	RECTANGULAR SQUARENESS ORTOGONALIDAD (MM)	±0.2%	±0.6%	UNI EN ISO 10545-2
	SURFACE FLATNESS PLANARIDAD (MM)	±0.2%	±0.5%	UNI EN ISO 10545-2
	THICKNESS (MM) ESPESOR	±2.0%	±5.0%	UNI EN ISO 10545-2
	WATER ABSORPTION ABSORCION DE AGUA	E ≤ 0.05 %	E ≤ 0.50 %	UNI EN ISO 10545-3
	BREAKING STRENGTH FUERZA DE ROTURA	2830 N	1113N	ASTM C-648
	CHEMICAL RESISTANCE RESISTENCIA A PRODUCTOS QUIMICOS	B	GB Para Esmaltados UB para Pulidos	EN 106
	STAIN RESISTANCE RESISTENCIA A LA MANCHAS	class-3	≥ Grado 3	UNI EN ISO 10545-14
	DEEP ABRASION RESISTANCE	<144 mm ³	<204 mm ³	EN 102
	MOHS HARDNESS DUREZA SUPERFICIAL (ESCALA MOHS)	>8	MOHS 1-10	EN 101

INFORMACION DE EMPAQUES

SIZE FORMATO	M2/BOX M2/CAJA	PCS./BOX PZA./CAJA	BOX/PALLET CAJA/PALETA	M2/PALLET M2/PALETA	KG/BOX KG/CAJA	KG/PALLET KG/PALETA	BOX/CNT CAJA/CONTENED	M2/CNT M2/CONTENED.
600X600X7 mm	1.44	4	48	69.12	22	1056	1188	1710.72

