

## CHEVRON



Model: CHEVRON WHITE, CHEVRON GREY, CHEVRON BLACK

Size:44X44 cm

Thickness: 10 mm

Material: PORCELANIC TILE

Technical Features		Referencial Normative
Manufacture Process	Single Fired Tiles	Dry Pressing ceramic tile
Thickness (mm.)	10	UNE EN ISO 10545 Part 2
Length. Width , density, straightness, flatness.	Fulfills the requirements applied to each model defined in the normative UNE-EN-14411 for Group Bla	UNE EN ISO 10545 Part 2
Water absorption	E<0.5 %	UNE EN ISO 10545 Part 3
Resistance to flexion (N/mm.2) and breaking strength (N)	>35 >1300	UNE EN ISO 10545 Part 4
Resistance to termal clash	Resists Test	UNE EN ISO 10545 Part 9
Resistance to crack	Resists Test	UNE EN ISO 10545 Part 11
Frost Resistance	Resists Test	UNE EN ISO 10545 Part 12

Chemical Resistance		
Domestic cleaning products	GA	UNE EN ISO 10545 Part 13
Swimming Pool Salt	GA	
Acids and bases (low concentration)	GLA/GHA	
Resistance to stains	Class 5	UNE EN ISO 10545 Part 14

Documentation with commercial information. It cannot be used for administrative nor judicial purposes without Realonda S.A authorization.

Colors of this piece on this technical card are illustrative and can differ from the real piece.